




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 29/02, 12/56, G06F 17/30		A1	(11) International Publication Number: WO 98/17039
			(43) International Publication Date: 23 April 1998 (23.04.98)
(21) International Application Number: PCT/SE97/01644		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 30 September 1997 (30.09.97)			
(30) Priority Data: 9603753-6 14 October 1996 (14.10.96) SE			
(71) Applicant (for all designated States except US): MIRROR IMAGE INTERNET AB [SE/SE]; P.O. Box 1043, S-101 38 Stockholm (SE).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): LINDBO, Sverker [SE/SE]; Björkliden 16, S-187 41 Täby (SE). LÖTHBERG, Peter [SE/SE]; Reijmersholmsgatan 29, S-117 40 Stockholm (SE). VIXIE, Paul [US/US]; 11400 La Honda Road, Star Route Box 159 A, Woodside, CA 94062 (US).			
(74) Agent: AWAPATENT AB; P.O. Box 45086, S-104 30 Stockholm (SE).			
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: INTERNET COMMUNICATION SYSTEM



(57) Abstract

The present invention relates to the transferring of information on the Internet, comprising: means (40) for storing information, corresponding to information provided at an Internet content provider (60), at respective alternative addresses of said storing means; means (20) for intercepting an information request from an Internet user directed to an Internet content provider; means for determining whether or not the intercepted request is directed to an information content provider having an associated alternative address on said storing means (40); and means for directing the request to said alternative address if such an alternative address exists.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNET COMMUNICATION SYSTEMTechnical field of invention

The present invention relates to a method and a system for transferring information on the Internet.

5 Background to the invention and Prior Art

Over the last few years, Internet has developed into the fastest growing means of communication and is predicted to be the main system for distributing information in the future. The Internet has become increasingly popular and the number of users is growing at a magnificent rate.

10 However, the popularity of the Internet, and especially the use of the Internet application World Wide Web, is putting the net under enormous capacity pressure. Traffic on the Internet doubles about every three months, with no signs of slowing down. This kind of exponential growth will eventually slow down, but several factors indicate that it is still far from any slowdown in growth.

Today, only a small fraction, about 3 to 5 percent, of all PCs have access to the Internet. It is believed that most of those who have made and will make the investment in a PC will eventually want access to the Internet. Furthermore, communication speeds between the user and the Internet infrastructure is increasing rapidly. The transition from 14.4 kbit/s modems to 28.8 kbit/s is just being completed as manufacturers announce new modems at 56 kbit/s. Other technologies such as ISDN (128 kbit/s), Cable TV modems (500-10,000 kbit/s) and xDSL (2,000 to 25,000 kbit/s) are emerging. Moreover, manufacturers of household electronics are launching low costs devices to give Internet World Wide Web access through television sets, telephones, etc.

35 These and other factors are all contributing in making it increasingly difficult to access information on the Internet, since the system is basically being overloaded. This problem is a fact both in USA and Europe,

but it is even more serious when passing information between USA and Europe. The transatlantic transmission capacity is too small to cope with the exploding Internet use.

5 Basically, there exists two conventional solutions to this problem. A first solution is to add more bandwidth and switching capacity, which is being done, but which carries huge costs and also faces significant technical problems. A second solution is to use so called
10 "caching" or "mirroring" techniques. The meaning of these definitions is somewhat undefined and is also in some cases somewhat overlapping. However, "caching" basically means to keep track of the Internet traffic and to keep copies of the most frequently accessed World Wide Web
15 files at a location closer to the user. Similarly, "mirroring" basically means to keep copies of specific World Wide Web files in a mirror server, independent of the access frequencies.

 These second solutions hence involve the providing
20 of a local copy of a World Wide Web Site of interest. For example, a copy of CNN's USA-based homepage may be provided in a cache or a mirror at a European "proxy" location, whereby European Internet users may access the CNN homepage without having to use the transatlantic communication link, thereby both attaining quicker access and at
25 the same time lowering the load on the transatlantic link.

 However, caching and mirroring also raises several technical problems. For example, current research show
30 that to be most efficient, the cache must be near the original information source. Caching is always more efficient closer to the information content provider server than closer to the user. The problem is that, depending on the popularity of each site, the actual
35 location of the most popular original information providers keep moving around. A cache would therefore need to be very big to be efficient.

Another problem is that the user must specify a location for the copies of the original content information, it being a cache or a mirror. Such a location is called a "proxy" and can be specified in all commonly
5 used softwares for web access. This user interaction is difficult to obtain, given the increasing diversity of web users.

Furthermore, if the proxy is very large, as is needed to provide for a large amount of content with ever
10 changing popularity, it will also, for economical reasons, need to cater for very many users. The proxy itself will then become a bottleneck, and access times may thus increase. Consequently, there exists a problem with the limited scalability of the proxy technique.

15

Summary of the invention

It is therefore an object of the invention to reduce the capacity constraints on the Internet.

Another object of the invention is to provide a
20 scaleable technology for reducing access time on the Internet which allows growth to a significantly larger amount of users and information traffic on the Internet.

According to the present invention, said objectives are achieved by a method and a system according to the
25 appended claims.

Hence, according the invention, there is provided a concept for transferring information on the Internet, comprising: intercepting an information request from an Internet user directed to an Internet information content
30 provider address; determining whether or not said request relates to an information content provider address providing information which is also provided at a corresponding alternative address; and directing said request either to said alternative address, if existing, or to
35 said information content provider address, if not, for providing the requested information to said user.

The invention is hence based on the use of a so called interceptor, or interceptor means, which is used to examine the information requests from a user to decide whether the same information exists in a copied form or
5 the like on a server means arranged locally with respect to said interceptor means.

Hence, information corresponding to at least part of the information provided at one or more Internet information content provider addresses, is provided at respective associated alternative addresses, preferably in a
10 local storing means such as a local cache or mirror, the arrangement of said alternative addresses providing easier access with respect to a Internet user;

Here, the term "locally" does not necessarily imply
15 locally in the geographical sense, but may just as well mean locally in a time or access sense. The essential feature being that the access to the "local" server is quicker, easier, more cost efficient, or in any other aspect more preferable than the access to the original
20 content provider.

Consequently, in a preferred embodiment of the invention, said storing means is arranged in direct communication with said intercepting means.

According to the invention, the user does not have
25 to decide whether it is preferable to use the alternative server or not. Instead this selection is performed by the interceptor, thereby essentially only making use of the local server when the requested information is actually provided thereon.

30 In order for the re-routing of the information requests to be effective, it is preferred that the interception means is arranged close to the user, preferably between said user and an Internet first switching point. Such an Internet first switching point is generally
35 provided by a so called Internet Service Provider, which for example may be the local phone company, such as Telia in Sweden. However, in different applications, it will

also or alternatively be preferred to arrange said intercepting means at a Border Router or at a so called Network Access Point.

According to yet another preferred embodiment of the invention, the interceptor comprises a look up table which includes a first list of information content provider addresses having associated corresponding alternative addresses, making it possible easily to determine whether or not the request relates to information possibly stored at an alternative address on said storing means. The first list may for example include a list of locally stored World Wide Web Sites, i.e. a list of IP-addresses.

The interceptor is hence arranged to receive the information request from the user and then to decide, by comparison with said list, whether the address of interest have a copy or the like thereof provided on the locally arranged server. If the answer is yes, the request is re-routed to an alternative address on the local server. If no, then the request is sent on "untouched" to the first switching point or directly to the Internet and so forth.

According to a preferred embodiment of the invention, only requests or frames referring to a specific communication format or application, corresponding to the type of information service provided on the local storing means, is intercepted. For example, only so called TCP-queries to the WWW port.

According to the invention, the user does not have to decide whether or not to use an alternative address. Instead, the interceptor keeps track of which addresses or information that are stored in a copied form at the local server and simply re-routs the request if there is a match between the requested information address and a locally arranged copy of at least part of the information held at the requested address.

This allows for the preferred scaleability of a system according to the invention, since the local server may be very large without slowing down the use of the server. The information request does not have to pass
5 through the local server, but merely be judged with respect to the list of addresses stored in the interceptor. A interceptor according to the invention may therefor be used in communication with several servers, which in turn may be arranged in an hierarchical memory
10 structure.

Furthermore, the said interceptor means may be constituted by several interceptors arranged in parallel and connected, preferably via high speed switching means, to the server or servers.

15 In order for the request to be easily directed to the correct location on the server or servers, in such a case when at least one alternative address exists, said look up table preferably further comprises a second list of corresponding alternative addresses being associated
20 with said information content provider addresses, for obtaining an alternative address corresponding to the request. When the interceptor decides that a copy of at least part of the information provided at the requested information address exists on one of the local servers,
25 the second list provides the exact location of said alternative address or information on the server, thereby allowing the request to be re-routed directly to the alternative address, without having to travel through the entire server in order to reach the address of interest.
30 This feature further increases the scaleability of a system according to the invention.

In some cases, it may be desired to provide copies of only part of the information content provided by an information content provider. In such a case, it is
35 preferred to pass the information request along to the original content provider if the request corresponds to

the part of the entire information content which in fact does not exists on the local server.

Hence, according to a preferred embodiment of the invention, there is provided a list storing information
5 indicating if all of the information at the respective information content provider addresses is provided at the associated corresponding alternative addresses or, if not, which part of said information is provided, or is not provided, at said at least one associated corre-
10 sponding alternative addresses. Consequently, the interceptor according to this embodiment is arranged to direct said information request to an applicable alternative address on the local server only if said alternative address provides the part of the information
15 which refers to said information request.

According to a further developed embodiment, this third list, or parts thereof, may be provided in connection with the local server. According to this embodiment, a request relating to a specific content
20 address, having an alternative address on said server, may be re-routed to the server even if the part of information of interest in fact does not exist in a copied form on the server. However, when received at the server, the request is checked against said third list
25 and then, since the relevant information in this case actually did not exist, is sent on to the original content provider. Consequently, some requests may be temporarily re-routed but still sent on to the original content provider. In a preferred embodiment, the part of
30 said third list relating to frequently visited sites is stored in connection with said interceptor means, and the part relating to less frequently visited sites is stored in connection with said storing means. This provides the advantage of faster processing achivable by said
35 interceptor and determining means.

The third list may for example include so called URL-addressen or addresspatterns of files or object that

are or are not mirrored at the alternative address.

According to yet another embodiment of the invention, there is provided means for updating the information at said alternative addresses. Preferably, 5 said updating means is arranged to update the information at said alternative addresses at specific time intervals. Alternatively, said updating means may be arranged to provide an updating signal from said information content provider address to said corresponding alternative 10 address for updating the information at the alternative address when requested.

According to a yet further embodiment of the invention, said local server may comprise processing means for controlling for example said updating of the 15 information at the alternative addresses. The server control unit or a interceptor control unit may be used to update said lists as the information content in the local storing means changes.

The invention provides many advantages compared to 20 prior art. For example, traffic can be redirected to the mirror server even if the user do not specify a proxy location or if the user deliberately tries to inactivate a proxy setting made by the Internet Service Provider.

The content on the local or mirror server can be 25 managed through a process known as "server push", whereby changes in the original content servers is "pushed" to the mirror server.

Further, there is no limit to the number of interceptors that may be used. Moreover, each interceptor may 30 point to any number of different servers for different parts of the mirrored content. Also, several mirror servers may be configured both in parallel at a given location, and in a geographic hierarchy.

In the event of a failure of an interceptor, it can 35 rapidly be bypassed to restore some service while the interceptor is being repaired or replaced.

In the event of a failure of a mirror server, or a disk subsystem or on a mirror server, the interceptor can be instructed to route the affected part of the traffic to the Internet, while the defective components are being repaired or replaced.

It is to be understood that the local storing means may function as a mirror as well as a cache, as long as an updated list of which sites that presently are stored on said storing means exists to be used by the interceptor for deciding whether or not to re-route the request.

Although the description of the invention has been made with respect to the Internet communication system, it is understood by those skilled in the art that the invention also may be used in other similar types of global information communication systems which may be found in the future and which may show similar kinds of communication problems. The invention is therefore of course not limited to the Internet application.

Also, even though the description further has been made mainly with respect to the World Wide Web application, it is to be understood that the invention may as well be used for many other kinds of net applications and is not limited thereto.

Furthermore, even though the invention has been described as comprising intercepting, determining, directing and other means, it is understood by those skilled in the art that these different elements do not necessarily need to be provided as single units, but may instead constitute part of each other or may be integrated in some form.

Brief description of the drawings

Further aspects, features and advantages of the invention will become clear from the following description of preferred exemplifying embodiments with reference to the accompanying drawings, in which:

Fig 1 schematically shows a block diagram of a first embodiment of a system according to the present invention;

Fig 2 schematically shows a block diagram of an embodiment of the interceptor in Fig 1;

Fig 3 schematically shows a block diagram of a second embodiment of a system according to the present invention; and

Fig 4 schematically shows a block diagram of a third embodiment of a system according to the present invention.

Detailed description of preferred embodiments

With reference to fig 1, a first embodiment of a system for communicating information on the Internet will now be described.

In Fig 1, a set of end user terminals or stations USR1 to USRN are connected to a multiplexing unit 10, which may be a modem pool or a LAN router depending on the type of user system. The multiplexing unit 10 is connected to an interceptor 20 which, in turn, is connected to an Internet first switching point 30 providing access to the Internet 50, said first switching point 30 generally being located at the premises of an Internet Service Provider. The multiplexing unit 10 multiplexes the communications to and from the user terminals USR1 to USRN.

According to this system, a user USR1 wishing to access information provided for example as a World Wide Web homepage or site by an Internet information content provider 60, located at a original site of publication somewhere on the Internet 50, generally sends an informa-

tion request, specifically a HTTP request to the WWW-port, via the multiplexing unit 10 to the Internet first switching point 30, where the request is routed out on the Internet 50 to finally reach the content provider 60.

5 The content provider 60 then answers the request, sending the requested information via the Internet 50 back to the user USR1.

However, according to the first embodiment of the invention shown in Fig 1, the information request from a user USR1 to USRN is intercepted by the interceptor 20 before it reaches the first switching point 30. The information request is then examined by the interceptor, which decides whether or not the requested information, for example the information provided by the content

15 provider 60, exist in a copy or similar form on a local server 40, often called a "mirror server", arranged in direct communication with the interceptor 20. If a copy or the like of the requested information provided by the content provider 60 is stored at the local server 40, the request from the user is re-routed to the server 40,

20 which will then return the requested information to the user. However, if the interceptor determines that no copy or the like of the information of interest exists on the local server 40, then the information request from the user USR1 to USRN is sent on to the Internet first switching point as in the conventional form of Internet communication.

25

Note that the interceptor 20 only intercepts communication packages of certain specific types. For example, in Fig 1, only World Wide Web information requests from the users USR1 to USRN is intercepted. Other types of communication services, such as e-mail or the like, is left undisturbed by the interceptor 20.

30

If a request is re-routed to the server 40, but the server 40 however is unable, perhaps temporarily, to answer the request due to some kind of failure or the like, or for example if the server only provides a copy

35

of part of the information stored at the original content provider address, said request referring to the "uncopied" part, the server is then arranged to pass on the request to the original content provider via the Internet 50
5 unaffected, thereby making sure that the user will get the information requested also in these types of situations. Also, the interceptor 20 is arranged so that the communication between the users USR1 to USRN and the first switching point 30 bypasses the interceptor 20 in
10 cases when the interceptor suffers from a failure, in order for the general communication to be left undisturbed in such cases.

The system is arranged to update the information provided by the mirror server 40. This can be performed
15 in many ways, as is understood by those skilled in the art. In one example, the interceptor 20 or the mirror server 40 is arranged to update the server 40 at specific time intervals, for example once a day. As is clear, different bases stored on the mirror server 40 may need
20 to be updated at different time intervals, depending on the rate that the information provided at the original content providers 60 is altered.

According to another example, the content provider 60 may be provided with a specific updating service unit
25 (not shown) which is arranged to send an updating signal to the mirror server 40 when the information provided by the original content provider 60 has been changed significantly, said change causing the service unit to decide that the mirror server need to be updated and hence send
30 the updating signal, in response to which the mirror server 40 is updated or performs an updating procedure.

An exemplifying embodiment of the interceptor 20 shown in Fig 1 will now be described with reference to Fig 2. In Fig 2, the interceptor 20 comprises a central
35 processing or control unit 25 which generally receives information packages from the user or users and sends on information packages to the first switching point in Fig

1. The interceptor 20 further comprises a memory 27 which stores a look up table comprising three lists A, B and C. The central processing unit 25 is hence also connected to the memory 27 and to the mirror server 40 in Fig 2.

5 The look up table in the form of the three lists A, B and C stored in the memory 27 provides information regarding which information that is to be found at which locations on the mirror server 40. More specifically, list A provides information as to which Internet content
10 providers (for example content provider 60 in Fig 1) are to be found in a copied or similar "mirrored" alternative form on the mirror server 40, for example a set of the most frequented IP-addresses. Further, list B provides information as to at which specific locations or addresses
15 the respective mirrored sites is to be found on the mirror server 40. Finally, list C provides information as to which part or parts of the full content of the information provided by the different original content providers 60 that are, or are not, provided at the mirrored
20 sites on the mirror server 40, for example a list of URL-patterns of files on these sites that for one reason or other is not mirrored.

As is indicated by the arrows in Fig 2, each field in the respective lists is associated with a specific
25 field in the other lists. For example, each IP-address in list A, referring to an original content provider 60, is associated to an associated specific mirror or alternative address on the mirror server 40 in list B and to a specific field of URL-patterns in list C that are not
30 mirrored at the mirror site.

An example of the operation of the interceptor 20 in Fig 1 and 2 will now be described. When the central processing unit 25 in the interceptor 20 receives or intercepts a message from a user, say USR1, it firstly checks
35 if the message is of a type of interest, i.e. if the message relates to the kind of information type stored on the mirror server 40, for example if the message is a IP

World Wide Web request. If the message is not of the relevant type, for example if its a e-mail message, it is sent on directly to the first switching point 30 without being affected by the interceptor 20.

5 However, if the message is of a relevant type, i.e. an IP WWW request, the central processing unit 25 accesses list A to determine whether or not the requested IP-address exist in list A, i.e. whether or not the requested IP-address exists in a mirrored form on the mirror
10 server 40. If the answer is no, i.e. if the request IP-address does not exist in list A, the request is sent on to the Internet first switching point 30. In such a case, the request is consequently left unaffected by the
interceptor.

15 However, if the answer is yes, i.e. if the request IP-address exists in list A, the central processing unit 25 accesses the associated field in list C to determine whether or not the entire content provider site is
20 mirrored on the mirror server or, if not, whether or not the requested information relates to the part or parts of the content provider information which do exist in a mirrored form on the mirror server 40.

 Then, if the requested information relates to a part of the original content provider information which is
25 determined not to exist on the mirror server 40, the central processing unit sends the request to the Internet first switching point 30 unaffected by the interceptor
20.

 However, if the relevant information is determined
30 to exist on the local mirror server 40, the central processing unit 25 accesses the associated field in list B in the memory 27 to derive information as to the specific location address of said information on the mirror
server 40. The central processing unit 25 then sends the
35 information request directly to this location address on the mirror server 40, which in respond to said request

provides the requested information back to the user USR1 via the central processing unit 25.

As is understood by those skilled in the art, the structure and operation of the central processing unit 25 and the look up table in the memory 27 may be realized in many different ways, the invention not being limited to the one described herein. For example, parts of said list C may be provided at the mirror server (not shown), whereby a request relating to an address included in the list A is re-routed to the server independent of whether or not the requested part of the mirrored information actually exists on the server. If, in fact, it doesn't, the server then simply sends the request along to the original content provider.

In Fig 3 and 4, for ease of description, elements corresponding to those already described with reference to Fig 1 and 2 will be designated with the same numerals, and description thereof is therefore omitted in the following.

In Fig 3, another embodiment of a system according to the invention is shown, wherein the storing means 40 is comprised of a set of mirror servers 41-45 arranged in a hierarchic structure, instead of using a single server as shown in Fig 1. If so desired, the separate mirror servers 41-45 may be arranged at different geographical or logical locations, thereby providing scaling and configuration flexibility. According to this embodiment, said list B of the interception memory 27 in Fig 2 is arranged to provide address information as to which server and which location thereon that is associated with the respective mirrored IP-addresses.

In Fig 4 there is shown an embodiment of a system according to the invention, wherein two separate user groups, USR1, USR2, ..., USRN and USR1', USR2', ..., USRN', are serviced by separate interceptors 20 and 20', respectively, via multiplexing devices 10 and 10', respectively. The intercepting means is hence comprised of

two (or more) identical interceptors 20, 20', each serving different user groups but making use of the same set of mirror servers 41-43. The respective interceptors 20, 20' communicates with the different mirror servers 41-43 via a high speed switch 70. In this embodiment, the interceptors 20 and 20' are both connected to the same Internet first switching point 30. However, the interceptors 20, 20' could just as well be connected to different Internet first switching points but still be using the same set of memory servers 41-43. According to this embodiment, an incoming request from a user is directed to the respective interceptor 20, 20' which re-routes, if so decided, the request to the relevant mirror server 41-43 via the high speed switch 70 or sends the request unaffected to the first switching point 30. The possibility to use several interceptors in the described manner further enhances the scaleability of a system according to the invention.

It is understood that the construction and function of the separate elements described with reference to the drawings will become apparent for those skilled in the art.

Even though the invention has been described with reference to specific exemplifying embodiments, many different alterations, modifications and the like will become apparent for those skilled in the art. The described embodiments are therefore not intended to limit the scope of the invention, as defined by the appended claims.

CLAIMS

1. Method for transferring information on the Internet, comprising the steps of:

5 intercepting an information request from an Internet user directed to a content provider address;

 determining whether or not said request relates to a content provider address having a corresponding alternative address, said alternative address providing at least
10 part of the information provided at said content provider address;

 directing said request to said corresponding alternative address, if existing, or to said content provider address, if not.

15

2. Method as claimed in claim 1, comprising providing at least part of the information provided at one or more content provider addresses at respective corresponding alternative addresses.

20

3. Method as claimed in claim 1 or 2, comprising passing on information sent from either said content provider address or said alternative address, as a result of said request, to said Internet user.

25

4. Method as claimed in any one of the preceding claims, comprising:

 providing a first list of information content provider addresses having respective corresponding
30 alternative addresses; and

 accessing said first list for determining whether or not it includes the content provider address which said request is referring to, thereby determining whether or not said request relates to a content provider address
35 having a corresponding alternative address.

5. Method as claimed in any one of the preceding claims, comprising:

providing a second list of said corresponding alternative addresses;

5 accessing said second list for, having determined that a corresponding alternative address for the requested information exists, obtaining said corresponding alternative address in order to direct said request thereto.

10

6. Method as claimed in any one of the preceding claims, wherein said steps comprises:

15 determining which part of said information provided at said content provider address that is provided, or is not provided, at said alternative address;

20 directing said request to said content provider address if said request refers to the the part of the information provided by said content provided address which is not provided at said alternative address; and
directing said request to said alternative address if said request refers to the the part of the information provided by said content provided address which is provided at said alternative address.

25 7. Method as claimed in any one of the preceding claims, further comprising:

30 providing a third list which includes information indicating if all the information at a content provider address is provided at a corresponding alternative address or, if not, which part of said information that is provided, or is not provided, at said corresponding alternative address;

35 accessing said third list for determining if said request refers to the part of said information which is provided at said alternative address; and

directing said request to said alternative address only if said alternative address provides the part of the information which refers to said information request.

5 8. Method as claimed in any one of the preceding claims, wherein said third list comprises URL-adresser or address patterns which are or are not provided at said corresponding alternative addresses.

10 9. Method as claimed in any one of the preceding claims, comprising intercepting said request before or at an Internet first, with respect to said user, switching point, said first switching point preferably being arranged at an Internet Service Provider.

15 10. Method as claimed in any one of the preceding claims, comprising updating the information at said alternative addresses according to a predefined scheme.

20 11. Method as claimed in any one of the preceding claims, comprising updating the information at said alternative addresses at specific time intervals.

25 12. Method as claimed in any one of the preceding claims, further comprising providing an updating signal from said information content provider address to said corresponding alternative address for updating the information at the alternative address when requested.

30 13. System for transferring information on the Internet, comprising:

 means (20) for intercepting an information request from an Internet user directed to a content provider address (60);

35 means (20; 20, 25, 27) for determining whether or not said request is directed to a content provider address having a corresponding alternative address, said

alternative address providing at least part of the information provided at said content provider address;

means (20; 20, 25, 27) for directing said information request to said corresponding alternative address, if such a corresponding alternative address exists, or to said content provider address, if not.

14. System as claimed in claim 13, comprising means (40) for storing said information, corresponding to at least part of the information provided at one or more content provider addresses (60), at respective associated alternative addresses of said storing means (40).

15. System as claimed in claim 13 or 14, wherein said intercepting means (20) is arranged to pass on information sent from either said content provider address (60) or said alternative address (40), as a result of said request, to said Internet user.

20. 16. System as claimed in claim 13, 14 or 15, wherein said determining and directing means constitute part of said intercepting means (20).

25. 17. System as claimed in claim 13, 14, 15 or 16, wherein said interception means (20) is arranged between said user and an Internet first switching point (30), said first switching point preferably being arranged at an Internet Service Provider.

30. 18. System as claimed in any one of claims 13-17, wherein said determining means comprises a first list (A) of content provider addresses having respective corresponding alternative addresses on said storing means (40), said determining means being arranged to access said first list (A) for determining whether or not the request relates to information provided at an alternative address on said storing means.

19. System as claimed in claim 18, comprising a second list (B), associated with said first list (A), of the corresponding alternative addresses which are associated with said information content provider addresses, said directing means being arranged to access said second list (B) for obtaining said alternative address corresponding to the requested information.

20. System as claimed in any one of claims 13-19, comprising a third list (C) storing information as to which part of said information, provided at the respective information content provider addresses (60), that is, or is not, provided at the associated corresponding alternative addresses (40), wherein said determining and directing means is arranged to direct said information request to said information content provider address (60), if said alternative address does not provide the part of the information which refers to said information request, or to said alternative address, if it does.

21. System as claimed in any one of claims 13-20, further comprising means for updating the information at said alternative addresses.

22. System as claimed in claim 21, wherein said updating means being arranged to update the information at said alternative addresses at specific time intervals.

23. System as claimed in claim 21 or 22, wherein said updating means is arranged to provide an updating signal from said information content provider address to said storing means for updating the information at the alternative address when requested.

24. System as claimed in any one of claims 13-23, wherein said storing means (40) comprises one or more servers (41-45).
- 5 25. System as claimed in any one of claims 13-24, wherein said intercepting means comprises two or more interceptors (20, 20') arranged to serve respective user groups (USR1-USRN, USR1'-USRN').
- 10 26. System as claimed in any one of claims 13-25, wherein said intercepting means (20; 20, 20') communicates with said storing means (40; 41-45) by means of high speed switching means (70).




FIG 1





FIG 2






FIG 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01644

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 29/02, H04L 12/56, G06F 17/30
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

INSPEC, WPIL, PASCAL

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	DATATEKNIK, Volume, No 8, April 1997, (Stockholm), Nordling, "Mirror Image bygger om nätet" page 45	1-26
A	JP 8241260 A (SONY CORP), 17 Sept 1996 (17.09.96), abstract	1-26
A	EP 0618708 A2 (INTERNATIONAL BUSINESS MACHINES CORPORATION), 5 October 1994 (05.10.94), abstract	1-26
A	EP 0674263 A1 (INTERNATIONAL BUSINESS MACHINES CORPORATION), 27 Sept 1995 (27.09.95), abstract	10-12,21-23

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
 "E" earlier document but published on or after the international filing date
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 "O" document referring to an oral disclosure, use, exhibition or other means
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

6 March 1998

Date of mailing of the international search report

09 -03- 1998

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Anders Ströbeck
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01644

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	JP 8278934 A (SONY CORP), 22 October 1996 (22.10.96), abstract -----	1-26

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SE 97/01644

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
JP	8241260	A	17/09/96	NONE	
EP	0618708	A2	05/10/94	JP 2511644 B JP 6309264 A US 5511208 A	03/07/96 04/11/94 23/04/96
EP	0674263	A1	27/09/95	JP 7262070 A US 5657440 A	13/10/95 12/08/97
JP	8278934	A	22/10/96	NONE	

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)